



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
4		BROKE OUT FROM KIT AS INDIVIDUAL TOOL.	8/21/2012	RJC	RW
5		CH'D T/N WAS RBEA94-3700-B IS RBE350A94-3700-B. -01 CH'D DIM WAS Ø.75 IS (Ø.75), WAS .083 IS (.083). -03 CH'D DIM WAS Ø.570 ∇ .079 IS Ø.570. ADDED DIM Ø.586 P.F. -01. (Ø.20). -05 CH'D DIM WAS Ø2.00 IS (Ø2.00), WAS Ø.586 P.F. -05 IS Ø.586 P.F. -01. CH'D TOLERANCE ON NON-CRITICAL PARTS.	5/23/2014	DPD	RJC
6	16-0151	UPDATED TO NEW DRAFTING STANDARD. DELETED P/N 8 , ADDED P/N'S -1A , -09 , -011 , -013 . CH'D -07 DESCRIPTION WAS SOCKET HEAD SET SCREW DOG POINT IS SOCKET HEAD SET SCREW EXTENDED POINT. -1A ADDED DRAWING. -01 , -03 , -05 ADDED FINISH SPEC QSMI-6.2.2. B.O. REV D. -01 CH'D DIM WAS (Ø.75) IS Ø.75, WAS (.083) IS .08. ADDED DIMS Ø.6047/.6040 (P.F. -03), Ø.6047/.6040 (P.F. -05), .88, .88, 2X .03 X 45°, ADDED ENGRAVE NOTE. -03 CH'D DIM WAS Ø.586 P.F. -01 IS Ø.6056/.6052 (P.F. -01). -05 CH'D DIM WAS Ø.586 P.F. -01 IS Ø.6056/.6052 (P.F. -01), WAS (Ø2.00) IS 2.00, CH'D MATERIAL WAS 1018 IS 1018/1020 CR.	2/24/2017	RJC	SM




ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
	X		-1A	3	SHORT BRACE ASSEMBLY			2
	1		-01		TUBE	STEEL		3
	1		-03		CAP	SP HEX		4
	1		-05		FOOT	1018/1020 CR		5
	1	B/O	-07		SOCKET HEAD SET SCREW, EXTENDED POINT	STEEL	M6 X 1 X 30mm (MCMASTER-CARR #92905A225)	2
	1	B/O	-09		REMOVE BEFORE FLIGHT	NYLON	NAS 1756-12	2
	1	B/O	-011		LANYARD CABLE	COATED STEEL	Ø1/16 X 8 (CARR LANE #CL-2-C)	2
	2	B/O	-013		FERRULE	ALUMINUM	Ø1/16 X 3/8 (MCMASTER-CARR #3896T31)	2
	ASSY -1A							

			
TITLE SWASHPLATE IMMOBILIZING TOOL SHORT BRACE ASSEMBLY			
DWG NO. RBE350A94-3700-B			REV 6
MAT'L		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125/✓	
HEAT TREAT			
FINISH			
SPEC			
DRAWN BY:	CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
CHECKED:	DUERFELDT		
OPPS APPR:	ANDERSON		
QA APPR:	LINDSAY	USED ON MODEL	
APPROVED:	MACKOVJAK	EUROCOPTER AS350/355	
SCALE	1:4	DATE	8/21/2012
			SHEET 1 OF 5

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
6	16-0151	-1A ADDED DRAWING.	2/24/20107	RJC	SM



NOTE:


1 LOCTITE -07 INTO -03.

-1A
SHORT BRACE ASSEMBLY

DART AEROSPACE	
TITLE SWASHPLATE IMMOBILIZING TOOL SHORT BRACE ASSEMBLY	
DWG NO. RBE350A94-3700-B-1A	REV 6
MAT'L HEAT TREAT FINISH SPEC	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125°
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	EUROCOPTER AS350/355
SCALE 1:5	DATE 8/21/2012
SHEET 2 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
5		-01 CH'D DIM WAS $\emptyset.75$ IS ($\emptyset.75$), WAS .083 IS (.083).	5/23/2014	DPD	RJC
6	16-0151	-01 CH'D DIM WAS ($\emptyset.75$) IS $\emptyset.75$, WAS (.083) IS .08. ADDED DIMS $\emptyset.6047/.6040$ (P.F. -.03), $\emptyset.6047/.6040$ (P.F. -.05), .88, .88, 2X .03 X 45°, ADDED ENGRAVE NOTE, ADDED FINISH SPEC QSMI-6.2.2, B.O. REV D.	2/24/2017	RJC	SM






(-01)
TUBE

DART AEROSPACE	
TITLE SWASHPLATE IMMOBILIZING TOOL SHORT BRACE ASSEMBLY	
DWG NO. RBE350A94-3700-B-01	REV 6
MAT'L STEEL HEAT TREAT FINISH BLACK OXIDE SPEC QMSI-6.2.2, B.O. REV D	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX \pm .005 FRACTIONS \pm 1/8 .XX \pm .01 ANGLES \pm 5° .X \pm .1 SURFACES = 125°	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: CLOUGH	USED ON MODEL
CHECKED: DUERFELDT	EUROCOPTER AS350/355
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:1	DATE 8/21/2012
SHEET 3 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
5		-03 CH'D DIM WAS Ø.570 ∇ .079 IS Ø.570, ADDED DIM Ø.586 P.F. -01, (Ø.20).	5/23/2014	DPD	RJC
6	16-0151	-03 CH'D DIM WAS Ø.586 P.F. -01 IS Ø.6056/.6052 (P.F. -01), ADDED FINISH SPEC QSMI-6.2.2, B.O. REV D.	2/24/2017	RJC	SM






(-03)
CAP

DART AEROSPACE	
TITLE SWASHPLATE IMMOBILIZING TOOL SHORT BRACE ASSEMBLY	
DWG NO. RBE350A94-3700-B-03	REV 6
MAT'L SP HEX	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX \pm .005 FRACTIONS \pm 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX \pm .01 ANGLES \pm 5°
DRAWN BY: CLOUGH	.X \pm .1 SURFACES = 125°
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 8/21/2012	USED ON MODEL
SHEET 4 OF 5	EUROCOPTER AS350/355

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
5		-05 CH'D DIM WAS Ø2.00 IS (Ø2.00), WAS Ø.586 P.F. -05 IS Ø.586 P.F. -01.	5/23/2014	DPD	RJC
6	16-0151	-05 CH'D DIM WAS Ø.586 P.F. -01 IS Ø.6056/.6052 (P.F. -01), WAS (Ø2.00) IS 2.00, ADDED FINISH SPEC QSMI-6.2.2, B.O. REV D, CH'D MATERIAL WAS 1018 IS 1018/1020 CR.	2/24/2017	RJC	SM



(-05)
FOOT

DART AEROSPACE	
TITLE SWASHPLATE IMMOBILIZING TOOL SHORT BRACE ASSEMBLY	
DWG NO. RBE350A94-3700-B-05	REV 6
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125°
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 8/21/2012	USED ON MODEL
SHEET 5 OF 5	EUROCOPTER AS350/355